NSN 5962-01-037-6783

Linear Microcircuit - Page 1 of 1



view Online at https://aerobasegroup.com/nsn/5962-01-037-6763
Body Length:
Between 0.875 inches and 0.925 inches
Body Width:
Between 0.460 inches and 0.520 inches
Body Height:
Between 0.130 inches and 0.150 inches
Maximum Power Dissipation Rating:
275.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Transmitting set, aircraft approach control type an/tpn-30
Features Provided:
Hermetically sealed and monolithic and negative outputs and positive outputs
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Dual-in-line
Input Circuit Pattern:
12 input
Design Function And Quantity:
1 converter, digital to analog
Terminal Surface Treatment:
Gold
Time Rating Per Chacteristic:
500.00 nanoseconds propagation delay time, low to high level output
Precious Material And Location:
Terminals gold
Precious Material:
Gold
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
Yes - demil/mli
Fiig:

A458a0