NSN 5962-01-037-8588

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-037-8588

Body Length:

Between 0.725 inches and 0.825 inches

Body Width:

Between 0.220 inches and 0.325 inches

Body Height:

0.205 inches

Maximum Power Dissipation Rating:

500.0 milliwatts

Operating Tempurature Range:

-55.0/+125.0 degrees celsius

Storage Tempurature Range:

-65.0/+150.0 degrees celsius

End Application:

Signal processer type cm-442a/alr-4 (v)

Features Provided:

Monolithic and true/complementary and high speed and adjustable and w/enable and negative outputs and positive outputs and hermetically

sealed and complementary outputs and unipolar

Inclosure Material:

Ceramic and metal

Inclosure Configuration:

Dual-in-line

Input Circuit Pattern:

12 input

Design Function And Quantity:

1 converter, digital to analog

Terminal Surface Treatment:

Tin

Time Rating Per Chacteristic:

60.00 nanoseconds propagation delay time, low to high level output and 60.00 nanoseconds propagation delay time, high to low level output

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0