

View Online at <https://aerobasegroup.com/nsn/5962-01-037-8592>

Body Length:

Between 0.745 inches and 0.785 inches

Body Width:

Between 0.240 inches and 0.280 inches

Body Height:

Between 0.120 inches and 0.160 inches

Maximum Power Dissipation Rating:

625.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hermetically sealed and monolithic and positive outputs and bipolar and 3-state output and w/enable and w/storage and w/buffered output and w/decoded output and w/disable and programmable and programmed and high speed

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

10 input

Case Outline Source And Designator:

-0-001-ae joint electron device engineering council

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

5.5 volts power source

Time Rating Per Characteristic:

35.00 nanoseconds propagation delay time, low to high level output and 35.00 nanoseconds propagation delay time, high to low level output

Memory Device Type:

Rom

Test Data Document:

36659-13046426l drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

16 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0