NSN 5962-01-039-0322

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-039-0322

| Body Outside Diameter: |
|--|
| Between 0.335 inches and 0.370 inches |
| Body Height: |
| Between 0.165 inches and 0.185 inches |
| Maximum Power Dissipation Rating: |
| 300.0 milliwatts |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| Features Provided: |
| High impedance and hermetically sealed and high gain and high slew rate and bipolar |
| Inclosure Material: |
| Metal |
| Inclosure Configuration: |
| Can |
| Input Circuit Pattern: |
| 2 input |
| Design Function And Quantity: |
| 1 amplifier, operational, general purpose |
| Case Outline Source And Designator: |
| To-99 joint electron device engineering council |
| Terminal Surface Treatment: |
| Solder |
| Voltage Rating And Type Per Characteristic: |
| 45.0 volts power source |
| Test Data Document: |
| 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). |
| Terminal Type And Quantity: |
| 8 pin |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |
| A458a0 |
| |