NSN 5962-01-039-3400

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-039-3400

Body Length:

Between 1.348 inches and 1.368 inches

Body Width:

Between 0.980 inches and 1.020 inches

Body Height:

Between 0.355 inches and 0.395 inches

Maximum Power Dissipation Rating:

600.0 milliwatts

Operating Tempurature Range:

-55.0/+125.0 degrees celsius

Storage Tempurature Range:

-65.0/+150.0 degrees celsius

End Application:

5825-00-279-3490

Features Provided:

Hermetically sealed and externally compensated and monolithic and negative outputs and positive outputs

Inclosure Material:

Metal

Inclosure Configuration:

Can

Input Circuit Pattern:

4 input

Design Function And Quantity:

1 amplifier, hybrid and 1 amplifier, operational, general purpose and 1 amplifier, power

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

15.0 volts power source

Time Rating Per Chacteristic:

4000.00 nanoseconds propagation delay time, low to high level output

Test Data Document:

94117-324009 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;

excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

8 pin

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A458a0