NSN 5962-01-039-3440

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-039-3440
Body Length:
Between 0.370 inches and 0.395 inches
Body Width:
Between 0.245 inches and 0.275 inches
Body Height:
Between 0.040 inches and 0.080 inches
Maximum Power Dissipation Rating:
400.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+200.0 degrees celsius
End Application:
Converter model 6514a fscm 35351
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Flat pack
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
6 input
Case Outline Source And Designator:
-0-004-ag joint electron device engineering council
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
6.0 volts power source
Time Rating Per Chacteristic:
50.00 nanoseconds propagation delay time, low to high level output
Memory Device Type:
Rom
Precious Material And Location:
Terminals gold
Test Data Document:
35351-151471 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
16 flat leads
Shelf Life:
N/a

--

Unit Of Measure:

NSN 5962-01-039-3440

Memory Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0