# NSN 5962-01-039-3464

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-039-3464

### **Body Length:**

Between 0.750 inches and 0.795 inches

### **Body Width:**

Between 0.245 inches and 0.300 inches

## **Body Height:**

Between 0.120 inches and 0.195 inches

### **Maximum Power Dissipation Rating:**

512.0 milliwatts

#### **Operating Tempurature Range:**

+0.0/+75.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+160.0 degrees celsius

#### End Application:

Data display group type ol-17 (v) /uyk

#### **Features Provided:**

Hermetically sealed and monolithic and high speed and negative outputs and positive outputs and programmable and programmed and

schottky and w/enable and w/open collector

#### **Inclosure Material:**

Ceramic and glass

#### Inclosure Configuration:

Dual-in-line

#### **Output Logic Form:**

Transistor-transistor logic

#### Input Circuit Pattern:

10 input

#### Case Outline Source And Designator:

-0-001-ag joint electron device engineering council

#### **Terminal Surface Treatment:**

Solder

## Voltage Rating And Type Per Characteristic:

5.5 volts power source

## Memory Device Type:

Ram

## Memory Capacity:

Unknown

## Test Data Document:

46859-398-15190 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,

etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

## Terminal Type And Quantity:

16 printed circuit

## Shelf Life:

N/a

## Unit Of Measure:

# NSN 5962-01-039-3464

Memory Microcircuit - Page 2 of 2

## Demilitarization:

Yes - demil/mli

Fiig:

A458a0

