## NSN 5962-01-039-3466

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-039-3466

Body Length:	
0.870 inches	
Body Width:	
Between 0.240 inches and 0.260 inches	
Body Height:	
0.180 inches	
Maximum Power Dissipation Rating:	
333.0 milliwatts	
Operating Tempurature Range:	
+0.0/+70.0 degrees celsius	
Storage Tempurature Range:	
-65.0/+150.0 degrees celsius	
End Application:	
Radio receiver type r-191 (v) 2/grr	
Features Provided:	
Expandable and high speed and monolithic and positive outputs and programmable and programmed and w/buffered output and w/de	coded
output and w/disable and w/enable and w/open collector	
Inclosure Material:	
Plastic	
Inclosure Configuration:	
Dual-in-line	
Output Logic Form:	
Transistor-transistor logic	
Input Circuit Pattern:	
6 input	
Terminal Surface Treatment:	
Silver	
Voltage Rating And Type Per Characteristic:	
5.5 volts power source	
Time Rating Per Chacteristic:	
50.00 nanoseconds propagation delay time, low to high level output and 50.00 nanoseconds propagation delay time, high to low lev	el
output	
Memory Device Type:	
Ram	
Memory Capacity:	
Unknown	
Precious Material And Location:	
Terminals silver	
Precious Material:	
Silver	
Test Data Document:	
05828-4827-0141 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing	ng,

etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

## Terminal Type And Quantity:

16 printed airquit

## NSN 5962-01-039-3466

Memory Microcircuit - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

Yes - demil/mli

Fiig:

A458a0

