

View Online at <https://aerobasegroup.com/nsn/5962-01-039-4754>

Body Length:

Between 0.240 inches and 0.260 inches

Body Width:

Between 0.120 inches and 0.150 inches

Body Height:

Between 0.030 inches and 0.070 inches

Maximum Power Dissipation Rating:

40.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

Receiving set, countermeasures type an/ulr-1 () (v)

Features Provided:

Hermetically sealed and monolithic and positive outputs and low power

Inclosure Material:

Glass and metal

Inclosure Configuration:

Flat pack

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

3 input

Design Function And Quantity:

1 multivibrator, monostable

Case Outline Source And Designator:

T0-84 joint electron device engineering council

Terminal Surface Treatment:

Gold

Voltage Rating And Type Per Characteristic:

5.5 volts power source

Time Rating Per Characteristic:

40.00 nanoseconds propagation delay time, low to high level output

Special Features:

Insulator furnished

Precious Material And Location:

Body gold and terminals gold

Precious Material:

Gold

Terminal Type And Quantity:

14 flat leads

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0