## NSN 5962-01-039-7300

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-039-7300

| Body Length:   |
|--|
| Between 0.370 inches and 0.390 inches  |
| Body Width:  |
| Between 0.248 inches and 0.252 inches  |
| Body Height:   |
| Between 0.128 inches and 0.132 inches  |
| Maximum Power Dissipation Rating:  |
| 680.0 milliwatts   |
| Operating Tempurature Range:   |
| +0.0/+70.0 degrees celsius   |
| Storage Tempurature Range:   |
| 65.0/+150.0 degrees celsius  |
| End Application:   |
| Receiver type rn262b   |
| Features Provided:   |
| Monolithic and internally compensated and negative outputs and positive outputs  |
| nclosure Material:   |
| Plastic  |
| nclosure Configuration:  |
| Dual-in-line   |
| nput Circuit Pattern:  |
| 2 input  |
| Design Function And Quantity:  |
| 1 amplifier, operational, general purpose  |
| Terminal Surface Treatment:  |
| Solder   |
| Voltage Rating And Type Per Characteristic:  |
| 18.0 volts power source  |
| Test Data Document:  |
| 27914-51008 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; |
| excludes any specification, standard or other document that may be referenced in a basic governing drawing)                            |
| Terminal Type And Quantity:  |
| 3 printed circuit  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| -  |
| Demilitarization:  |
| Yes - demil/mli  |
| Filg:  |
| M58a0  |