## NSN 5962-01-039-7322

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-039-7322

**Body Length:** 

Between 0.750 inches and 0.795 inches

**Body Width:** 

Between 0.245 inches and 0.300 inches

**Body Height:** 

Between 0.120 inches and 0.195 inches

**Maximum Power Dissipation Rating:** 

625.0 milliwatts

**Operating Tempurature Range:** 

+0.0/+75.0 degrees celsius

Storage Tempurature Range:

-65.0/+150.0 degrees celsius

**End Application:** 

Cheyenne aircraft model 427m

**Features Provided:** 

Bipolar and hermetically sealed and high speed and monolithic and positive outputs and programmable and programmed and w/buffered output and w/decoded output and w/disable and w/enable and w/storage and 3-state output

**Inclosure Material:** 

Ceramic and glass

**Inclosure Configuration:** 

Dual-in-line

**Output Logic Form:** 

Transistor-transistor logic

**Input Circuit Pattern:** 

10 input

**Case Outline Source And Designator:** 

-0-001-ag joint electron device engineering council

**Terminal Surface Treatment:** 

Solder

Voltage Rating And Type Per Characteristic:

5.5 volts power source

**Time Rating Per Chacteristic:** 

30.00 nanoseconds propagation delay time, low to high level output and 30.00 nanoseconds propagation delay time, high to low level output

**Memory Device Type:** 

Ram

**Memory Capacity:** 

Unknown

**Test Data Document:** 

11530-278539 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:** 

16 printed circuit

Shelf Life:

. . .

## NSN 5962-01-039-7322

Memory Microcircuit - Page 2 of 2



			ure:	

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0