NSN 5962-01-039-9419

Digital Microcircuit - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5962-01-039-9419 |
|---|
| Body Length: |
| Between 0.750 inches and 0.795 inches |
| Body Width: |
| Between 0.245 inches and 0.300 inches |
| Body Height: |
| Between 0.120 inches and 0.195 inches |
| Maximum Power Dissipation Rating: |
| 625.0 milliwatts |
| Operating Tempurature Range: |
| +0.0/+75.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| End Application: |
| Cheyenne aircraft model 427m |
| Features Provided: |
| Bipolar and hermetically sealed and high speed and monolithic and positive outputs and programmable and programmed and w/buffered |
| output and w/decoded output and w/disable and w/enable and w/storage and 3-state output |
| Inclosure Material: |
| Ceramic and glass |
| Inclosure Configuration: |
| Dual-in-line |
| Output Logic Form: |
| Transistor-transistor logic |
| Input Circuit Pattern: |
| 10 input |
| Case Outline Source And Designator: |
| -0.001-ag joint electron device engineering council |
| Time Rating Per Chacteristic: |
| 30.00 nanoseconds propagation delay time, low to high level output and 30.00 nanoseconds propagation delay time, high to low level |
| output |
| Test Data Document: |
| 11530-278539 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; |
| excludes any specification, standard or other document that may be referenced in a basic governing drawing) |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |

Fiig:

A458a0