# NSN 5962-01-040-0757

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-040-0757

## **Body Length:**

Between 0.660 inches and 0.785 inches

## **Body Width:**

Between 0.220 inches and 0.280 inches

## **Body Height:**

Between 0.140 inches and 0.180 inches

#### **Operating Tempurature Range:**

+0.0/+70.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

#### **End Application:**

Data display group type ol-17 (v) /uyk

#### Features Provided:

Hermetically sealed and monolithic and negative outputs and positive outputs and w/strobe

#### **Inclosure Material:**

## Ceramic and glass

# Inclosure Configuration:

Dual-in-line

#### **Input Circuit Pattern:**

3 input

## **Design Function And Quantity:**

2 driver, line

## Case Outline Source And Designator:

T0-116 joint electron device engineering council

#### **Terminal Surface Treatment:**

Solder

#### Voltage Rating And Type Per Characteristic:

15.0 volts power source

#### Time Rating Per Chacteristic:

60.00 nanoseconds propagation delay time, low to high level output and 45.00 nanoseconds propagation delay time, high to low level output

#### **Terminal Type And Quantity:**

14 printed circuit

#### Shelf Life:

N/a

# Unit Of Measure:

---

## Demilitarization:

Yes - demil/mli

## Fiig:

A458a0