NSN 5962-01-040-1427



Linear Microcircuit - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5962-01-040-1427 **Body Outside Diameter:** Between 0.335 inches and 0.370 inches **Body Height:** Between 0.165 inches and 0.185 inches **Maximum Power Dissipation Rating:** 630.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** Indicator, frequency type ip-1270/grr-3 (v) **Features Provided:** Hermetically sealed and monolithic and externally compensated and high speed and bipolar and high current and negative outputs and positive outputs **Inclosure Material:** Glass and metal **Inclosure Configuration:** Can **Input Circuit Pattern:** 2 input **Design Function And Quantity:** 1 amplifier, wideband **Case Outline Source And Designator:** T0-99 joint electron device engineering council **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 15.0 volts power source **Time Rating Per Chacteristic:** 600.00 nanoseconds propagation delay time, low to high level output **Terminal Type And Quantity:** 8 pin Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

Fiig:

A458a0