

View Online at <https://aerobasegroup.com/nsn/5962-01-040-6384>

Body Length:

Between 1.200 inches and 1.290 inches

Body Width:

Between 0.515 inches and 0.580 inches

Body Height:

Between 0.100 inches and 0.180 inches

Maximum Power Dissipation Rating:

455.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hermetically sealed and monolithic and darlington-connected and w/disable and w/enable and positive outputs

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

14 input

Design Function And Quantity:

1 arithmetic logic unit and 1 generator, function

Case Outline Source And Designator:

-0-015-aa joint electron device engineering council

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

5.5 volts power source

Time Rating Per Characteristic:

50.00 nanoseconds propagation delay time, low to high level output and 50.00 nanoseconds propagation delay time, high to low level output

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

24 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0