## NSN 5962-01-040-8250

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-040-8250 **Body Length:** 0.850 inches **Body Width:** 0.280 inches **Body Height:** 0.200 inches **Maximum Power Dissipation Rating:** 300.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** Test set, detecting-ranging set type an/aqm-22 **Features Provided:** Hermetically sealed and monolithic and negative outputs and positive outputs and high gain and w/enable and programmable and externally compensated **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** 4 channel **Design Function And Quantity:** 4 amplifier, operational, general purpose **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 10.0 volts power source **Time Rating Per Chacteristic:** 1500.00 nanoseconds propagation delay time, low to high level output **Test Data Document:** 77068-3195528 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 16 printed circuit Shelf Life: N/a **Unit Of Measure:** 

Fiig: A458a0

**Demilitarization:** Yes - demil/mli