NSN 5962-01-040-8260

Digital Microcircuit - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5962-01-040-8260 |
|---|
| Body Length: |
| Between 3.990 inches and 4.000 inches |
| Body Width: |
| Between 1.990 inches and 2.000 inches |
| Body Height: |
| Between 0.395 inches and 0.405 inches |
| Operating Tempurature Range: |
| +0.0/+85.0 degrees celsius |
| Storage Tempurature Range: |
| -55.0/+85.0 degrees celsius |
| End Application: |
| Receiving set, countermeasures type an/wlr- (v) 2 |
| Features Provided: |
| Hybrid and negative outputs and positive outputs and w/enable and resettable and unipolar |
| Inclosure Material: |
| Plastic |
| Inclosure Configuration: |
| Dual-in-line |
| Output Logic Form: |
| Transistor-transistor logic |
| Input Circuit Pattern: |
| 5 input |
| Design Function And Quantity: |
| 1 converter, analog to digital |
| Terminal Surface Treatment: |
| Gold |
| Voltage Rating And Type Per Characteristic: |
| 15.0 volts power source |
| Precious Material And Location: |
| Terminals gold |
| Precious Material: |
| Gold |
| Test Data Document: |
| 07397-32-811588 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing |
| etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) |
| Terminal Type And Quantity: |
| 25 printed circuit |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

Demilitarization:

Yes - demil/mli

NSN 5962-01-040-8260

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0