NSN 5962-01-041-8052

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-041-8052

view Online at https://acrobasegroup.com/nsn/0302-01-041-0002
Body Length:
Between 0.376 inches and 0.384 inches
Body Width:
Between 0.245 inches and 0.271 inches
Body Height:
Between 0.140 inches and 0.185 inches
Maximum Power Dissipation Rating:
800.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and monolithic and high speed and positive outputs
Inclosure Material:
Glass and metal
Inclosure Configuration:
Dual-in-line
Input Circuit Pattern:
Dual 2 input
Design Function And Quantity:
2 driver, peripheral
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-1.5 volts power source and 5.5 volts power source
Time Rating Per Chacteristic:
35.00 nanoseconds propagation delay time, low to high level output and 35.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
8 printed circuit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

Fiig:

A458a0