NSN 5962-01-041-8055

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-041-8055
Body Length:
Between 0.660 inches and 0.730 inches
Body Width:
Between 0.220 inches and 0.280 inches
Body Height:
Between 0.120 inches and 0.150 inches
Operating Tempurature Range:
-55.0/+85.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Monitor, television type ip-1252/axq-13 and camera, television type mx-9784/axq-13
Features Provided:
Hermetically sealed and monolithic and negative outputs and positive outputs and resettable and w/enable and synchronous
Inclosure Material:
Glass and metal
Inclosure Configuration:
Dual-in-line
Input Circuit Pattern:
5 input
Design Function And Quantity:
1 generator
Terminal Surface Treatment:
Gold
Voltage Rating And Type Per Characteristic:
-17.0 volts power source and 5.3 volts power source
Time Rating Per Chacteristic:
750.00 nanoseconds propagation delay time, low to high level output and 750.00 nanoseconds propagation delay time, high to low level
output
Precious Material And Location:
Terminals gold
Precious Material:
Gold
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
16 printed circuit
Shelf Life:
N/a

Demilitarization:

Unit Of Measure:

Yes - demil/mli

NSN 5962-01-041-8055

Linear Microcircuit - Page 2 of 2



Fiig:

A458a0