NSN 5962-01-041-8063

Digital Microcircuit - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5962-01-041-8063 |
|----------------------------------------------------------------------------------------------------------------------------------------------|
| Body Length: |
| 0.440 inches |
| Body Width: |
| Between 0.245 inches and 0.285 inches |
| Body Height: |
| Between 0.045 inches and 0.085 inches |
| Maximum Power Dissipation Rating: |
| 286.0 milliwatts |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| End Application: |
| Radar set type an/tpn-30 |
| Features Provided: |
| Hermetically sealed and monolithic and positive outputs and resettable and retriggerable and w/clear and complementary outputs and dual |
| edge triggered |
| Inclosure Material: |
| Ceramic and glass |
| Inclosure Configuration: |
| Flat pack |
| Output Logic Form: |
| Transistor-transistor logic |
| Input Circuit Pattern: |
| Dual 5 input |
| Design Function And Quantity: |
| 2 multivibrator, monostable |
| Case Outline Source And Designator: |
| F-5 mil-m-38510 |
| Terminal Surface Treatment: |
| Tin |
| Voltage Rating And Type Per Characteristic: |
| -1.5 volts power source and 5.5 volts power source |
| Test Data Document: |
| 81349-mil-m-39510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Terminal Type And Quantity: |
| 16 printed circuit |

N/a **Unit Of Measure:**

Shelf Life:

Specification Data:

81349-mil-m-39510/12 government specification

NSN 5962-01-041-8063

Digital Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0