

View Online at <https://aerobasegroup.com/nsn/5962-01-041-8065>

**Body Length:**

Between 0.740 inches and 0.870 inches

**Body Width:**

Between 0.220 inches and 0.310 inches

**Body Height:**

Between 0.139 inches and 0.204 inches

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

Receiving set, countermeasures type an/wlr- (v) 2

**Features Provided:**

Hermetically sealed and monolithic and bipolar and w/buffered output and w/decoded output and w/enable and w/disable and w/storage and positive outputs and programmable and programmed

**Inclosure Material:**

Ceramic and glass

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Transistor-transistor logic

**Input Circuit Pattern:**

10 input

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

-1.0 volts power source and 5.5 volts power source

**Time Rating Per Characteristic:**

125.00 nanoseconds propagation delay time, low to high level output and 65.00 nanoseconds propagation delay time, high to low level output

**Memory Device Type:**

Rom

**Test Data Document:**

07397-15-808654 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

16 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0