# NSN 5962-01-042-2171

Memory Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-042-2171

# **Body Length:**

Between 0.750 inches and 0.785 inches

# **Body Width:**

Between 0.220 inches and 0.280 inches

# **Body Height:**

Between 0.140 inches and 0.180 inches

## **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

## Storage Tempurature Range:

-65.0/+150.0 degrees celsius

## **Features Provided:**

Hermetically sealed and monolithic and negative outputs and positive outputs and w/enable and programmable and programmed and bipolar

and w/buffered output and w/decoded output and expandable and wire-or outputs

#### Inclosure Material:

Ceramic and glass

#### **Inclosure Configuration:**

Dual-in-line

#### **Output Logic Form:**

Transistor-transistor logic

#### **Input Circuit Pattern:**

6 input

## **Terminal Surface Treatment:**

Solder

## Voltage Rating And Type Per Characteristic:

-1.5 volts power source and 5.5 volts power source

## **Time Rating Per Chacteristic:**

50.00 nanoseconds propagation delay time, low to high level output

#### Memory Device Type:

Rom

#### **Memory Capacity:**

Unknown

#### **Test Data Document:**

94990-51-+01424e drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,

etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

#### **Terminal Type And Quantity:**

16 printed circuit

#### Shelf Life:

N/a

# Unit Of Measure:

--

#### Demilitarization:

Yes - demil/mli

# Fiig:

A458a0