NSN 5962-01-042-5372

Memory Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-042-5372

View Online at https://aerobasegroup.com/nsn/5962-01-042-5372
Body Length:
Between 0.750 inches and 0.785 inches
Body Width:
Between 0.220 inches and 0.280 inches
Body Height:
Between 0.140 inches and 0.180 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and monolithic and negative outputs and positive outputs and w/enable and programmable and programmed and bipolar
and w/buffered output and w/decoded output and expandable and wire-or outputs
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
6 input
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-1.5 volts power source and 5.5 volts power source
Time Rating Per Chacteristic:
50.00 nanoseconds propagation delay time, low to high level output
Memory Device Type:
Rom
Memory Capacity:
Unknown
Test Data Document:
94990-51-+01424e drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
16 printed circuit
Shelf Life:
N/a
Unit Of Measure:

Fiig: A458a0

Demilitarization: Yes - demil/mli