NSN 5962-01-043-6186

Digital-linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-043-6186 **Body Length:** Between 0.750 inches and 0.785 inches **Body Width:** Between 0.240 inches and 0.295 inches **Body Height:** 0.180 inches **Maximum Power Dissipation Rating:** 1000.0 milliwatts **Operating Tempurature Range:** +0.0/+70.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and high speed and monolithic and negative outputs and positive outputs and w/inhibit **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** 5 input **Design Function And Quantity:** 4 driver, line **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 7.0 volts power source **Time Rating Per Chacteristic:** 25.00 nanoseconds propagation delay time, low to high level output and 25.00 nanoseconds propagation delay time, high to low level output **Terminal Type And Quantity:** 16 printed circuit Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

Yes - demil/mli

Fiig:

A458a0