NSN 5962-01-043-6186

Digital-linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-043-6186

Body Length:

Between 0.750 inches and 0.785 inches

Body Width:

Between 0.240 inches and 0.295 inches

Body Height:

0.180 inches

Maximum Power Dissipation Rating:

1000.0 milliwatts

Operating Tempurature Range:

+0.0/+70.0 degrees celsius

Storage Tempurature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hermetically sealed and high speed and monolithic and negative outputs and positive outputs and w/inhibit

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Dual-in-line

Input Circuit Pattern:

5 input

Design Function And Quantity:

4 driver, line

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

7.0 volts power source

Time Rating Per Chacteristic:

25.00 nanoseconds propagation delay time, low to high level output and 25.00 nanoseconds propagation delay time, high to low level output

Terminal Type And Quantity:

16 printed circuit

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A458a0