# NSN 5962-01-043-6195

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-043-6195

## **Body Length:**

Between 0.770 inches and 0.808 inches

## Body Width:

Between 0.278 inches and 0.298 inches

## **Body Height:**

Between 0.085 inches and 0.124 inches

## **Maximum Power Dissipation Rating:**

260.0 milliwatts

### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

### **Features Provided:**

Hermetically sealed and monolithic and positive outputs and w/enable and low power and w/storage and w/decoded output

### **Inclosure Material:**

## Ceramic and glass

## Inclosure Configuration:

Dual-in-line

## **Output Logic Form:**

N-type metal oxide-semiconductor logic

## **Input Circuit Pattern:**

13 input

## **Terminal Surface Treatment:**

Solder

## Voltage Rating And Type Per Characteristic:

7.0 volts power source

## **Time Rating Per Chacteristic:**

200.00 nanoseconds propagation delay time, low to high level output and 200.00 nanoseconds propagation delay time, high to low level output

### Memory Device Type:

Ram

#### Memory Capacity:

Unknown

#### Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

#### Terminal Type And Quantity:

16 printed circuit

#### Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

Yes - demil/mli

# NSN 5962-01-043-6195

Memory Microcircuit - Page 2 of 2

**Fiig:** A458a0

