## NSN 5962-01-043-6200

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-043-6200

View Offiline at https://derobasegroup.com/risin/0302-01-040-0200
Body Length:
Between 0.350 inches and 0.400 inches
Body Width:
Between 0.200 inches and 0.300 inches
Body Height:
Between 0.008 inches and 0.100 inches
Maximum Power Dissipation Rating:
525.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and monolithic and positive outputs and high speed and schottky and w/enable and adjustable
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Flat pack
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
Dual 4 input
Design Function And Quantity:
2 oscillator, voltage controlled
Case Outline Source And Designator:
-0-004-ag joint electron device engineering council
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
5.5 volts power source
Test Data Document:
96906-mil-std-883  standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
16 flat leads
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

Fiig:

A458a0