NSN 5962-01-043-7917



Memory Microcircuit - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5962-01-043-7917 **Body Length:** Between 1.190 inches and 1.230 inches **Body Width:** Between 0.580 inches and 0.610 inches **Body Height:** Between 0.080 inches and 0.120 inches **Operating Tempurature Range:** +0.0/+70.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and monolithic and negative outputs and positive outputs and w/enable and w/storage and w/strobe and programmable and programmed and w/decoded output and w/disable and bipolar and 3-state output and high speed **Inclosure Material:** Ceramic and metal **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 11 input **Terminal Surface Treatment:** Gold **Voltage Rating And Type Per Characteristic:** -0.5 volts power source and 6.0 volts power source **Time Rating Per Chacteristic:** 50.00 nanoseconds propagation delay time, low to high level output and 50.00 nanoseconds propagation delay time, high to low level output **Memory Device Type:** Rom **Memory Capacity: Precious Material And Location:** Terminals gold and body gold **Precious Material:** Gold **Terminal Type And Quantity:** 24 printed circuit Shelf Life:

Demilitarization: Yes - demil/mli

Unit Of Measure:

N/a

NSN 5962-01-043-7917

Memory Microcircuit - Page 2 of 2



Fiig:

A458a0