NSN 5962-01-043-7920

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-043-7920 **Body Length:** Between 0.770 inches and 0.810 inches **Body Width:** Between 0.278 inches and 0.300 inches **Body Height:** Between 0.090 inches and 0.135 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** Countermeasures set type an/tlq-17a **Features Provided:** Hermetically sealed and monolithic and positive outputs and schottky and high speed and w/enable and programmable and w/decoded output and 3-state output and w/storage **Inclosure Material:** Ceramic and metal **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 10 input **Time Rating Per Chacteristic:** 30.00 nanoseconds propagation delay time, low to high level output and 30.00 nanoseconds propagation delay time, high to low level output **Precious Material And Location:** Terminals gold and body gold **Precious Material:** Gold **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Shelf Life: N/a **Unit Of Measure: Demilitarization:**

Yes - demil/mli

Fiig:

A458a0