NSN 5962-01-044-3764

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-044-3764

3, 14, 15, 16, 16, 16, 16, 16, 16, 16, 16, 16, 16
Body Length:
Between 1.244 inches and 1.256 inches
Body Width:
Between 0.698 inches and 0.704 inches
Body Height:
Between 0.250 inches and 0.340 inches
Maximum Power Dissipation Rating:
2.4 watts
Operating Tempurature Range:
55.0/+150.0 degrees celsius
Storage Tempurature Range:
65.0/+150.0 degrees celsius
End Application:
Countermeasures set type an/tlq-17a
Features Provided:
Hermetically sealed and monolithic and negative outputs and positive outputs and fixed and externally compensated and high power
nclosure Material:
Glass and metal
nclosure Configuration:
Can
nput Circuit Pattern:
5 input
Design Function And Quantity:
2 regulator, tracking
Case Outline Source And Designator:
T0-66 joint electron device engineering council
Terminal Surface Treatment:
Gold
Voltage Rating And Type Per Characteristic:
30.0 volts power source
Precious Material And Location:
Terminals gold
Precious Material:
Gold
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Ferminal Type And Quantity:
9 pin
Shelf Life:
N/a
Jnit Of Measure:

--

NSN 5962-01-044-3764

Linear Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0