NSN 5962-01-044-4125

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-044-4125 **Body Length:** Between 0.660 inches and 0.730 inches **Body Width:** Between 0.220 inches and 0.280 inches **Body Height:** Between 0.120 inches and 0.150 inches **Operating Tempurature Range:** -55.0/+85.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** Monitor, television type @ip-1252/axq-13 and camera, television type mx-9784/axq-13 **Features Provided:** Hermetically sealed and monolithic and negative outputs and positive outputs and resettable and w/enable and synchronous **Inclosure Material:** Glass and metal **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** 5 input **Terminal Surface Treatment:** Gold **Voltage Rating And Type Per Characteristic:** -17.0 volts power source and 5.3 volts power source **Time Rating Per Chacteristic:** 750.00 nanoseconds propagation delay time, low to high level output and 750.00 nanoseconds propagation delay time, high to low level output **Precious Material And Location:** Terminals gold and body gold **Precious Material:** Gold **Terminal Type And Quantity:** 16 printed circuit Shelf Life: N/a **Unit Of Measure: Demilitarization:**

Fiig:

A458a0

Yes - demil/mli