NSN 5962-01-044-4128

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-044-4128

Body	Length:

Between 1.188 inches and 1.212 inches

Body Width:

Between 0.565 inches and 0.590 inches

Body Height:

Between 0.110 inches and 0.160 inches

Operating Tempurature Range:

-55.0/+125.0 degrees celsius

Storage Tempurature Range:

-65.0/+150.0 degrees celsius

End Application:

Countermeasures set type an/tlq-17a

Features Provided:

Hermetically sealed and monolithic and positive outputs and schottky and high speed and w/enable and programmable and w/decoded output and 3-state output and w/storage

Inclosure Material:

Ceramic and metal

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

13 input

Terminal Surface Treatment:

Gold

Voltage Rating And Type Per Characteristic:

-0.5 volts power source and 5.5 volts power source

Time Rating Per Chacteristic:

30.00 nanoseconds propagation delay time, low to high level output and 30.00 nanoseconds propagation delay time, high to low level output

Memory Device Type:

Rom

Memory Capacity:

Unknown

Precious Material And Location:

Terminals gold and body gold

Precious Material:

Gold

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

24 printed circuit

Shelf Life:

N/a

NSN 5962-01-044-4128

Memory Microcircuit - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0