# NSN 5962-01-044-4608

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-044-4608

### **Body Length:**

0.440 inches

#### **Body Width:**

Between 0.245 inches and 0.285 inches

#### **Body Height:**

Between 0.045 inches and 0.085 inches

#### **Maximum Power Dissipation Rating:**

385.0 milliwatts

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

#### **Features Provided:**

Hermetically sealed and monolithic and positive outputs and high speed and schottky and w/decoded output and w/strobe and w/totem pole output

# Inclosure Material:

Ceramic and glass

## Inclosure Configuration:

Flat pack

#### **Output Logic Form:**

Transistor-transistor logic

#### **Input Circuit Pattern:**

Dual 6 input

#### **Design Function And Quantity:**

2 multiplexer, four to one line

#### **Case Outline Source And Designator:**

F-5 mil-m-38510

#### **Terminal Surface Treatment:**

Solder

#### Voltage Rating And Type Per Characteristic:

-1.2 volts power source and 5.5 volts power source

#### **Test Data Document:**

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### Terminal Type And Quantity:

16 flat leads

**Specification Data:** 

81349-mil-m-38510/79 government specification

#### Shelf Life:

N/a

#### Unit Of Measure:

- --
- Demilitarization:

# **NSN 5962-01-044-4608** Digital Microcircuit - Page 2 of 2

Fiig: A458a0

