

View Online at <https://aerobasegroup.com/nsn/5962-01-044-4610>

**Body Length:**

Between 0.350 inches and 0.400 inches

**Body Width:**

Between 0.200 inches and 0.300 inches

**Body Height:**

Between 0.008 inches and 0.100 inches

**Maximum Power Dissipation Rating:**

450.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**Features Provided:**

Hermetically sealed and monolithic and positive outputs and high speed and schottky and edge triggered and w/clear and w/enable

**Inclosure Material:**

Ceramic and glass

**Inclosure Configuration:**

Flat pack

**Output Logic Form:**

Transistor-transistor logic

**Input Circuit Pattern:**

8 input

**Design Function And Quantity:**

6 flip-flop, clocked and 6 flip-flop, d-type

**Case Outline Source And Designator:**

-0-004-ag joint electron device engineering council

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

-1.2 volts power source and 5.5 volts power source

**Time Rating Per Characteristic:**

15.00 nanoseconds propagation delay time, low to high level output and 22.00 nanoseconds propagation delay time, high to low level output

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

16 flat leads

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0