## NSN 5962-01-044-8965

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-044-8965

| Body Length:   |
|--|
| 1.252 inches   |
| Body Width:  |
| 0.700 inches   |
| Body Height:   |
| Between 0.250 inches and 0.340 inches  |
| Maximum Power Dissipation Rating:  |
| 2.4 watts  |
| Operating Tempurature Range:   |
| -55.0/+125.0 degrees celsius   |
| Storage Tempurature Range:   |
| -65.0/+150.0 degrees celsius   |
| Features Provided:   |
| Monolithic and hermetically sealed and negative outputs and positive outputs and externally compensated and adjustable |
| Inclosure Material:  |
| Glass and metal  |
| Inclosure Configuration:   |
| Can  |
| Input Circuit Pattern:   |
| 7 input  |
| Design Function And Quantity:  |
| 2 regulator, voltage   |
| Terminal Surface Treatment:  |
| Gold   |
| Voltage Rating And Type Per Characteristic:  |
| 30.0 volts power source  |
| Precious Material And Location:  |
| Terminals gold   |
| Precious Material:   |
| Gold   |
| Test Data Document:  |
| 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).     |
| Terminal Type And Quantity:  |
| 9 pin  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| -  |
| Demilitarization:  |
| Yes - demil/mli  |
| Fiig:  |
| A458a0   |
|  |