NSN 5962-01-045-3318

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-045-3318

Boty Length: Between 1.230 inches and 1.290 inches Body Width: Between 0.515 inches and 0.575 inches Body Height: Between 0.125 inches and 0.200 inches Maximum Power Dissipation Rating: 20.0 milliwatts Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -55.0/+150.0 degrees celsius Features Provided: Monolithic and hermetically sealed and negative outputs and positive outputs and multichip and bipolar and unipolar and adjustal Inclosure Material: Ceramic and glass Inclosure Configuration: Dual-in-line Input Circuit Pattern: 16 input Design Function And Quantity: 1 converter, digital to analog Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -15.0 volts power source and 15.0 volts power source Time Rating Per Chacteristic: 400.00 nanoseconds propagation delay time, low to high level output Terminal Type And Quantity:
Body Witth: Between 0.515 inches and 0.575 inches Body Height: Between 0.125 inches and 0.200 inches Maximum Power Dissipation Rating: 20.0 milliwatts Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -55.0/+150.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius Features Provided: Monolithic and hermetically sealed and negative outputs and positive outputs and multichip and bipolar and unipolar and adjustal Inclosure Material: Ceramic and glass Inclosure Configuration: Dual-in-line Input Circuit Pattern: 16 input Design Function And Quantity: 1 converter, digital to analog Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -15.0 volts power source and 15.0 volts power source Time Rating Per Chacteristic: 400.00 nanoseconds propagation delay time, low to high level output Terminal Type And Quantity:
Between 0.515 inches and 0.575 inches Body Height: Between 0.125 inches and 0.200 inches Maximum Power Dissipation Rating: 20.0 milliwatts Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -55.0/+150.0 degrees celsius Features Provided: Monolithic and hermetically sealed and negative outputs and positive outputs and multichip and bipolar and unipolar and adjustal inclosure Material: Ceramic and glass Inclosure Configuration: Dual-in-line Input Circuit Pattern: 16 input Design Function And Quantity: 1 converter, digital to analog Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -15.0 volts power source and 15.0 volts power source Time Rating Per Chacteristic: 400.00 nanoseconds propagation delay time, low to high level output Terminal Type And Quantity:
Body Height: Between 0.125 inches and 0.200 inches Maximum Power Dissipation Rating: 20.0 milliwatts Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -55.0/+150.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius Features Provided: Monolithic and hermetically sealed and negative outputs and positive outputs and multichip and bipolar and unipolar and adjustal inclosure Material: Ceramic and glass Inclosure Configuration: Dual-in-line Input Circuit Pattern: 16 input Design Function And Quantity: 1 converter, digital to analog Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -15.0 volts power source and 15.0 volts power source Time Rating Per Chacteristic: 400.00 nanoseconds propagation delay time, low to high level output Terminal Type And Quantity:
Between 0.125 inches and 0.200 inches Maximum Power Dissipation Rating: 20.0 milliwatts Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -55.0/+150.0 degrees celsius Features Provided: Monolithic and hermetically sealed and negative outputs and positive outputs and multichip and bipolar and unipolar and adjustal Inclosure Material: Ceramic and glass Inclosure Configuration: Dual-in-line Input Circuit Pattern: 16 input Design Function And Quantity: 1 converter, digital to analog Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -15.0 volts power source and 15.0 volts power source Time Rating Per Chacteristic: 400.00 nanoseconds propagation delay time, low to high level output Terminal Type And Quantity:
Maximum Power Dissipation Rating: 20.0 milliwatts Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -55.0/+150.0 degrees celsius Features Provided: Monolithic and hermetically sealed and negative outputs and positive outputs and multichip and bipolar and unipolar and adjustal Inclosure Material: Ceramic and glass Inclosure Configuration: Dual-in-line Input Circuit Pattern: 16 input Design Function And Quantity: 1 converter, digital to analog Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -15.0 volts power source and 15.0 volts power source Time Rating Per Chacteristic: 400.00 nanoseconds propagation delay time, low to high level output Terminal Type And Quantity:
20.0 milliwatts Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -55.0/+150.0 degrees celsius Features Provided: Monolithic and hermetically sealed and negative outputs and positive outputs and multichip and bipolar and unipolar and adjustal Inclosure Material: Ceramic and glass Inclosure Configuration: Dual-in-line Input Circuit Pattern: 16 input Design Function And Quantity: 1 converter, digital to analog Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -15.0 volts power source and 15.0 volts power source Time Rating Per Chacteristic: 400.00 nanoseconds propagation delay time, low to high level output Terminal Type And Quantity:
Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -55.0/+150.0 degrees celsius Features Provided: Monolithic and hermetically sealed and negative outputs and positive outputs and multichip and bipolar and unipolar and adjustal Inclosure Material: Ceramic and glass Inclosure Configuration: Dual-in-line Input Circuit Pattern: 16 input Design Function And Quantity: 1 converter, digital to analog Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -15.0 volts power source and 15.0 volts power source Time Rating Per Chacteristic: 400.00 nanoseconds propagation delay time, low to high level output Terminal Type And Quantity:
Storage Tempurature Range: -55.0/+150.0 degrees celsius Features Provided: Monolithic and hermetically sealed and negative outputs and positive outputs and multichip and bipolar and unipolar and adjustal Inclosure Material: Ceramic and glass Inclosure Configuration: Dual-in-line Input Circuit Pattern: 16 input Design Function And Quantity: 1 converter, digital to analog Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -15.0 volts power source and 15.0 volts power source Time Rating Per Chacteristic: 400.00 nanoseconds propagation delay time, low to high level output Terminal Type And Quantity:
Storage Tempurature Range: -55.0/+150.0 degrees celsius Features Provided: Monolithic and hermetically sealed and negative outputs and positive outputs and multichip and bipolar and unipolar and adjustal Inclosure Material: Ceramic and glass Inclosure Configuration: Dual-in-line Input Circuit Pattern: 16 input Design Function And Quantity: 1 converter, digital to analog Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -15.0 volts power source and 15.0 volts power source Time Rating Per Chacteristic: 400.00 nanoseconds propagation delay time, low to high level output Terminal Type And Quantity:
Features Provided: Monolithic and hermetically sealed and negative outputs and positive outputs and multichip and bipolar and unipolar and adjustal Inclosure Material: Ceramic and glass Inclosure Configuration: Dual-in-line Input Circuit Pattern: 16 input Design Function And Quantity: 1 converter, digital to analog Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -15.0 volts power source and 15.0 volts power source Time Rating Per Chacteristic: 400.00 nanoseconds propagation delay time, low to high level output Terminal Type And Quantity:
Features Provided: Monolithic and hermetically sealed and negative outputs and positive outputs and multichip and bipolar and unipolar and adjustal Inclosure Material: Ceramic and glass Inclosure Configuration: Dual-in-line Input Circuit Pattern: 16 input Design Function And Quantity: 1 converter, digital to analog Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -15.0 volts power source and 15.0 volts power source Time Rating Per Chacteristic: 400.00 nanoseconds propagation delay time, low to high level output Terminal Type And Quantity:
Monolithic and hermetically sealed and negative outputs and positive outputs and multichip and bipolar and unipolar and adjustal Inclosure Material: Ceramic and glass Inclosure Configuration: Dual-in-line Input Circuit Pattern: 16 input Design Function And Quantity: 1 converter, digital to analog Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -15.0 volts power source and 15.0 volts power source Time Rating Per Chacteristic: 400.00 nanoseconds propagation delay time, low to high level output Terminal Type And Quantity:
Inclosure Material: Ceramic and glass Inclosure Configuration: Dual-in-line Input Circuit Pattern: 16 input Design Function And Quantity: 1 converter, digital to analog Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -15.0 volts power source and 15.0 volts power source Time Rating Per Chacteristic: 400.00 nanoseconds propagation delay time, low to high level output Terminal Type And Quantity:
Ceramic and glass Inclosure Configuration: Dual-in-line Input Circuit Pattern: 16 input Design Function And Quantity: 1 converter, digital to analog Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -15.0 volts power source and 15.0 volts power source Time Rating Per Chacteristic: 400.00 nanoseconds propagation delay time, low to high level output Terminal Type And Quantity:
Inclosure Configuration: Dual-in-line Input Circuit Pattern: 16 input Design Function And Quantity: 1 converter, digital to analog Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -15.0 volts power source and 15.0 volts power source Time Rating Per Chacteristic: 400.00 nanoseconds propagation delay time, low to high level output Terminal Type And Quantity:
Dual-in-line Input Circuit Pattern: 16 input Design Function And Quantity: 1 converter, digital to analog Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -15.0 volts power source and 15.0 volts power source Time Rating Per Chacteristic: 400.00 nanoseconds propagation delay time, low to high level output Terminal Type And Quantity:
Input Circuit Pattern: 16 input Design Function And Quantity: 1 converter, digital to analog Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -15.0 volts power source and 15.0 volts power source Time Rating Per Chacteristic: 400.00 nanoseconds propagation delay time, low to high level output Terminal Type And Quantity:
Design Function And Quantity: 1 converter, digital to analog Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -15.0 volts power source and 15.0 volts power source Time Rating Per Chacteristic: 400.00 nanoseconds propagation delay time, low to high level output Terminal Type And Quantity:
Design Function And Quantity: 1 converter, digital to analog Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -15.0 volts power source and 15.0 volts power source Time Rating Per Chacteristic: 400.00 nanoseconds propagation delay time, low to high level output Terminal Type And Quantity:
1 converter, digital to analog Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -15.0 volts power source and 15.0 volts power source Time Rating Per Chacteristic: 400.00 nanoseconds propagation delay time, low to high level output Terminal Type And Quantity:
Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -15.0 volts power source and 15.0 volts power source Time Rating Per Chacteristic: 400.00 nanoseconds propagation delay time, low to high level output Terminal Type And Quantity:
Voltage Rating And Type Per Characteristic: -15.0 volts power source and 15.0 volts power source Time Rating Per Chacteristic: 400.00 nanoseconds propagation delay time, low to high level output Terminal Type And Quantity:
Voltage Rating And Type Per Characteristic: -15.0 volts power source and 15.0 volts power source Time Rating Per Chacteristic: 400.00 nanoseconds propagation delay time, low to high level output Terminal Type And Quantity:
-15.0 volts power source and 15.0 volts power source Time Rating Per Chacteristic: 400.00 nanoseconds propagation delay time, low to high level output Terminal Type And Quantity:
Time Rating Per Chacteristic: 400.00 nanoseconds propagation delay time, low to high level output Terminal Type And Quantity:
400.00 nanoseconds propagation delay time, low to high level output Terminal Type And Quantity:
Terminal Type And Quantity:
24 printed circuit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A458a0