## NSN 5962-01-046-3619

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-046-3619
Body Length:
Between 0.660 inches and 0.785 inches
Body Width:
Between 0.220 inches and 0.280 inches
Body Height:
Between 0.145 inches and 0.185 inches
Maximum Power Dissipation Rating:
500.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Artillery fire direction system, type an/gsg-1 (v)
Features Provided:
Hermetically sealed and monolithic and positive outputs
Inclosure Configuration:
Dual-in-line Dual-in-line
Input Circuit Pattern:
Quad 2 input
Design Function And Quantity:
4 driver, lamp, incandescent
Terminal Surface Treatment:
Gold or tin
Voltage Rating And Type Per Characteristic:
-2.0 volts power source and 30.0 volts power source
Precious Material And Location:
Terminals gold
Precious Material:
Gold
Test Data Document:
13973-862203 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
14 printed circuit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

Fiig:

A458a0

Yes - demil/mli