NSN 5962-01-046-3626



Digital Microcircuit - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5962-01-046-3626 **Overall Width:** Between 0.940 inches and 0.960 inches **Body Length:** Between 0.371 inches and 0.400 inches **Body Width:** Between 0.247 inches and 0.285 inches **Body Height:** Between 0.050 inches and 0.080 inches **Maximum Power Dissipation Rating:** 210.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and burn in and w/clock and complementary outputs **Inclosure Material:** Ceramic **Inclosure Configuration:** Flat pack **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 12 input **Design Function And Quantity:** 1 shift register, parallel load **Terminal Surface Treatment:** Solder **Time Rating Per Chacteristic:** 31.00 nanoseconds propagation delay time, low to high level output and 40.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 03640-6088909 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

Yes - demil/mli

Fiig:

A458a0