# NSN 5962-01-046-4786

Memory Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-046-4786

## Body Length:

Between 0.750 inches and 0.770 inches

## Body Width:

Between 0.260 inches and 0.280 inches

## **Body Height:**

Between 0.140 inches and 0.160 inches

## **Operating Tempurature Range:**

+0.0/+75.0 degrees celsius

## Storage Tempurature Range:

-65.0/+150.0 degrees celsius

## Features Provided:

Monolithic and hermetically sealed and positive outputs and programmable and programmed and bipolar and w/decoded output and expandable and wire-or outputs and 3-state output and w/buffered output and high speed and w/disable and w/enable

### Inclosure Material:

Ceramic and glass

#### Inclosure Configuration:

Dual-in-line

#### **Output Logic Form:**

Transistor-transistor logic

#### **Input Circuit Pattern:**

10 input

#### **Terminal Surface Treatment:**

Solder

#### Voltage Rating And Type Per Characteristic:

-1.0 volts power source and 5.5 volts power source

#### **Time Rating Per Chacteristic:**

70.00 nanoseconds propagation delay time, low to high level output and 70.00 nanoseconds propagation delay time, high to low level output

#### Memory Device Type:

Rom

#### **Memory Capacity:**

Unknown

#### Test Data Document:

97384-56602-40003 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

#### Terminal Type And Quantity:

16 printed circuit

#### Shelf Life:

N/a

### Unit Of Measure:

---

#### Demilitarization:

Yes - demil/mli

# Fiig: