NSN 5962-01-046-9448

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-046-9448
Body Length:
Between 0.250 inches and 0.260 inches
Body Width:
Between 0.140 inches and 0.260 inches
Body Height:
Between 0.035 inches and 0.050 inches
Maximum Power Dissipation Rating:
400.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and monolithic and negative outputs and positive outputs
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Flat pack
Input Circuit Pattern:
Dual 3 input
Design Function And Quantity:
2 receiver, line
Terminal Surface Treatment:
Gold
Voltage Rating And Type Per Characteristic:
-15.0 volts power source and 7.5 volts power source
Time Rating Per Chacteristic:
100.00 nanoseconds propagation delay time, low to high level output and 100.00 nanoseconds propagation delay time, high to low level
output
Precious Material And Location:
Terminal surfaces gold
Precious Material:
Gold
Test Data Document:
$99380-0073-544\ drawing\ (this\ is\ the\ basic\ governing\ drawing,\ such\ as\ a\ contractor\ drawing,\ original\ equipment\ manufacturer\ drawing,\ etc.;$
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
14 flat leads
Shelf Life:
N/a
Unit Of Measure:

Demilitarization: Yes - demil/mli

NSN 5962-01-046-9448

Linear Microcircuit - Page 2 of 2



Fiig:

A458a0