

View Online at <https://aerobasegroup.com/nsn/5962-01-046-9470>

**Body Length:**

Between 0.740 inches and 0.780 inches

**Body Width:**

Between 0.240 inches and 0.270 inches

**Body Height:**

Between 0.135 inches and 0.165 inches

**Maximum Power Dissipation Rating:**

180.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+175.0 degrees celsius

**Features Provided:**

Hermetically sealed and monolithic and negative outputs and resettable and edge triggered

**Inclosure Material:**

Ceramic and glass

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Emitter-coupled logic

**Input Circuit Pattern:**

Dual 5 input

**Design Function And Quantity:**

2 flip-flop, j-k/r-s, clocked

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

-5.2 volts power source and 0.0 volts power source

**Time Rating Per Characteristic:**

10.50 nanoseconds propagation delay time, low to high level output and 10.50 nanoseconds propagation delay time, high to low level output

**Test Data Document:**

80063-sm-d-732394 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

16 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0