

View Online at <https://aerobasegroup.com/nsn/5962-01-047-4923>

**Body Length:**

Between 0.750 inches and 0.795 inches

**Body Width:**

Between 0.245 inches and 0.300 inches

**Body Height:**

Between 0.140 inches and 0.195 inches

**Maximum Power Dissipation Rating:**

93.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**Features Provided:**

Hermetically sealed and hermetically sealed and low power and monolithic and positive outputs and presettable and programmable and schottky and synchronous and w/clear and w/disable and w/enable

**Inclosure Material:**

Ceramic and glass

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Transistor-transistor logic

**Input Circuit Pattern:**

9 input

**Design Function And Quantity:**

1 counter, binary

**Case Outline Source And Designator:**

-0-001-ag joint electron device engineering council

**Time Rating Per Characteristic:**

35.00 nanoseconds propagation delay time, low to high level output and 35.00 nanoseconds propagation delay time, high to low level output

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0