# NSN 5962-01-047-8234

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-047-8234 **Body Length:** 0.796 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** Between 0.150 inches and 0.185 inches **Maximum Power Dissipation Rating:** 570.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** Radar set, type an/fpn-62 **Features Provided:** Hermetically sealed and monolithic and internally compensated and positive outputs **Inclosure Material:** Glass and metal **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** Quad 2 input **Design Function And Quantity:** 

4 amplifier, operational, general purpose

### **Terminal Surface Treatment:**

Gold

# **Voltage Rating And Type Per Characteristic:**

36.0 volts power source

#### **Precious Material And Location:**

Body gold and terminals gold

### **Precious Material:**

Gold

## **Test Data Document:**

49956-913430 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

# **Terminal Type And Quantity:**

14 printed circuit

### Shelf Life:

N/a

# **Unit Of Measure:**

--

#### **Demilitarization:**

Yes - demil/mli

# NSN 5962-01-047-8234

Linear Microcircuit - Page 2 of 2



Fiig:

A458a0