## NSN 5962-01-048-1286

Linear Microcircuit - Page 1 of 1



| view Online at https://aerobasegroup.com/nsn/5962-01-046-1266  |
|--|
| Body Outside Diameter:   |
| Between 0.345 inches and 0.365 inches  |
| Maximum Power Dissipation Rating:  |
| 300.0 milliwatts   |
| Operating Tempurature Range:   |
| -55.0/+125.0 degrees celsius   |
| Storage Tempurature Range:   |
| -65.0/+150.0 degrees celsius   |
| Features Provided:   |
| Hermetically sealed and monolithic and high slew rate and fast settling and high gain and w/resiston |
| Inclosure Material:  |
| Metal  |
| Inclosure Configuration:   |
| Can  |
| Input Circuit Pattern:   |
| 2 input  |
| Design Function And Quantity:  |
| 1 amplifier, operational, general purpose  |
| Current Rating Per Characteristic:   |
| 6.00 milliamperes reverse current, dc absolute   |
| Terminal Surface Treatment:  |
| Solder   |
| Voltage Rating And Type Per Characteristic:  |
| 40.0 volts power source  |
| Terminal Type And Quantity:  |
| 8 pin  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| Yes - demil/mli  |
| Fiig:  |
| A458a0   |