NSN 5962-01-048-2961

Linear Microcircuit - Page 1 of 1

A458a0



View Online at https://aerobasegroup.com/nsn/5962-01-048-2961

view Offilite at https://aerobasegroup.com/hsi//0302-01-040-2301
Body Outside Diameter:
Between 0.597 inches and 0.603 inches
Body Height:
Between 0.160 inches and 0.170 inches
Maximum Power Dissipation Rating:
1.5 watts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and hybrid and negative outputs and positive outputs and adjustable
Inclosure Material:
Glass and metal
Inclosure Configuration:
Can
Input Circuit Pattern:
2 input
Design Function And Quantity:
1 amplifier, sample/hold
Terminal Surface Treatment:
Gold
Voltage Rating And Type Per Characteristic:
-15.0 volts power source and 15.0 volts power source
Time Rating Per Chacteristic:
100000.00 nanoseconds propagation delay time, low to high level output
Precious Material And Location:
Terminal surfaces gold
Precious Material:
Gold
Test Data Document:
03640-6088709 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
12 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig: