## NSN 5962-01-048-3766

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-048-3766

View Online at https://aerobasegroup.com/nsn/5962-01-048-3766
Body Length:
Between 0.780 inches and 0.820 inches
Body Width:
Between 0.275 inches and 0.310 inches
Body Height:
Between 0.080 inches and 0.150 inches
Maximum Power Dissipation Rating:
1.0 watts
Operating Tempurature Range:
+0.0/+70.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Receiving set, countermeasures type an/flr-1 ()
Features Provided:
Monolithic and hermetically sealed and positive outputs and w/enable
Inclosure Material:
Ceramic and metal
Inclosure Configuration:
Dual-in-line
Output Logic Form:
N-type metal oxide-semiconductor logic
Input Circuit Pattern:
7 input
Design Function And Quantity:
2 shift register, dynamic
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-0.5 volts power source and 7.0 volts power source
Time Rating Per Chacteristic:
50.00 nanoseconds propagation delay time, low to high level output and 50.00 nanoseconds propagation delay time, high to low level
output
Terminal Type And Quantity:
16 printed circuit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

Fiig:

A458a0

Yes - demil/mli