## NSN 5962-01-048-7762

Linear Microcircuit - Page 1 of 2



view Online at https://aerobasegroup.com/hsn/5962-01-046-7762
Body Length:
Between 0.240 inches and 0.260 inches
Body Width:
Between 0.240 inches and 0.260 inches
Body Height:
Between 0.050 inches and 0.065 inches
Maximum Power Dissipation Rating:
500.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Receiving set, panoramic data type an/apr-38
Features Provided:
Hermetically sealed and monolithic and negative outputs and positive outputs and bipolar and unipolar
Inclosure Material:
Ceramic and metal
Inclosure Configuration:
Flat pack
Input Circuit Pattern:
6 input
Design Function And Quantity:
1 converter, digital to analog
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
18.0 volts power source
Time Rating Per Chacteristic:
3000.00 nanoseconds propagation delay time, low to high level output
Precious Material And Location:
Terminal surfaces gold
Precious Material:
Gold
Test Data Document:
03640-6088702 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
14 flat leads
Shelf Life:
N/a

**Unit Of Measure:** 

## NSN 5962-01-048-7762

Linear Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0