Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-048-7763

Body Length:

1.800 inches

Body Width:

1.200 inches

Body Height:

0.200 inches

Operating Tempurature Range:

-55.0/+125.0 degrees celsius

Storage Tempurature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Monolithic and negative outputs and positive outputs

Inclosure Material:

Glass and plastic

Inclosure Configuration:

Dual-in-line

Input Circuit Pattern:

1 input

Design Function And Quantity:

1 amplifier, radio frequency

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

18.0 volts power source

Time Rating Per Chacteristic:

60.00 nanoseconds propagation delay time, low to high level output

Precious Material And Location:

Terminal surfaces gold

Precious Material:

Gold

Test Data Document:

30003-247as-c1757 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,

etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

6 printed circuit

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A458a0