# NSN 5962-01-048-7767

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-048-7767

#### **Body Outside Diameter:**

Between 0.335 inches and 0.370 inches

**Body Height:** 

Between 0.165 inches and 0.185 inches

**Maximum Power Dissipation Rating:** 

330.0 milliwatts

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### **Storage Tempurature Range:**

-65.0/+150.0 degrees celsius

**End Application:** 

Radar set type an/fpn-62 & ()

#### **Features Provided:**

Hermetically sealed and monolithic and negative outputs and positive outputs and adjustable

**Inclosure Material:** 

Glass and metal

#### **Inclosure Configuration:**

Can

#### **Input Circuit Pattern:**

2 input

## **Design Function And Quantity:**

1 comparator, voltage, differential

#### **Case Outline Source And Designator:**

A-1 mil-m-38510

#### **Terminal Surface Treatment:**

Solder

#### **Voltage Rating And Type Per Characteristic:**

15.0 volts power source

#### **Time Rating Per Chacteristic:**

600.00 nanoseconds propagation delay time, low to high level output and 500.00 nanoseconds propagation delay time, high to low level output

#### **Precious Material And Location:**

Terminal surfaces gold

#### **Precious Material:**

Gold

#### **Test Data Document:**

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Terminal Type And Quantity:**

8 pin

## Specification Data:

81349-mil-m-38510/103 government specification

Shelf Life:

NI/o

# NSN 5962-01-048-7767

Linear Microcircuit - Page 2 of 2



		eas	

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0