NSN 5962-01-048-7776

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-048-7776

| Overall Height: |
|--|
| 0.330 inches |
| Body Length: |
| Between 0.755 inches and 0.785 inches |
| |
| Body Width: Between 0.245 inches and 0.280 inches |
| |
| Body Height: 0.180 inches |
| |
| Maximum Power Dissipation Rating: 225.0 milliwatts |
| |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| Features Provided: |
| Hermetically sealed and monolithic and w/strobe |
| Inclosure Material: |
| Ceramic Include: Configuration: |
| Inclosure Configuration: |
| Dual-in-line Output Levie Forms |
| Output Logic Form: |
| Transistor-transistor logic |
| Input Circuit Pattern: |
| 9 input |
| Design Function And Quantity: |
| 1 selector, data, multiplexer |
| Time Rating Per Chacteristic: |
| 18.00 nanoseconds propagation delay time, low to high level output and 18.00 nanoseconds propagation delay time, high to low level |
| output D |
| Specification Data: |
| 20418-es5690-02 manufacturers source control |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |
| A458a0 |